

Laser Marking System

# Videojet® 3330

The 3330 30-Watt laser offers a powerful combination of performance and flexibility delivering high quality marks on moderate to high speed lines.

High speed packaging operations that demand crisp, high quality codes can rely on the performance of the 3330.

With virtually no font, code or graphic restrictions and line speeds up to 900 m/min., the 3330 is an ideal solution for marking complex codes at high speeds in food, beverage, cosmetics, pharmaceutical and extrusion industries.

Through a diverse combination of marking heads, lenses and wavelength options, Videojet can deliver 21 spot size variations to match a broad range of marking effects.



## Uptime Advantage

- Maximum performance and extended laser source life expectancy up to 45,000 hours through optimized total power output
- Air-cooled laser source virtually eliminates maintenance intervals
- Line set-up wizard aids fast product changeovers, eliminating set up trial and error and minimizing planned downtime\*

## Built-in productivity

- Large selection of mark window options offers optimally matched applications for faster marking
- On-screen diagnostics track causes of downtime and help troubleshooting to get the line back up and running quickly\*
- High speed capability allows marking at 150,000 products per hour

## Code Assurance

- Optional CLARiTY Laser Controller offers built-in software features that help reduce operator errors, to ensure products are coded correctly
- High quality, permanent codes help assure product traceability and tamper-proofing
- High resolution marking head delivers consistent, crisp codes

## Simple usability

- Most flexible integration solution with 32 standard beam delivery options
- Quick set up and easy redeployment via detachable umbilical cable for easy routing on the line and simple-to-use accessory connections
- 4 interface options plus a choice of networking communications to match your preferred workflow

\* With optional CLARiTY Laser Controller

# Videojet® 3330

## Laser Marking System

### Marking speed

Up to 1,300 characters/sec.<sup>(1)</sup>

### Line speed

Up to 15 m/sec. (49 feet/sec.)<sup>(1)</sup>

### Marking window

Approx. 25x20 mm to 485x351 mm

### Wavelengths

10.6µm, 10.2µm and 9.3µm

### Marking formats

Standard industrial fonts (Type 1 Windows® TrueType®) and Single line fonts  
Machine readable codes (OCR, 2D-matrix, etc.)  
Bar codes: BC25, BC251, BC39, BC128, GS1-128, EAN13, UPC\_A, RSS14, RSS14 Truncated, RSS14 Stacked, RSS14 Stacked Omnidirectional, RSS Limited, RSS Expanded, etc.  
Graphics, logos, symbols, etc.  
Linear, circular, angular, reverse, rotate  
Sequential and batch numbering  
Automatic date, layer and time coding; real-time clock  
Dot mode enables marking 2D codes faster than traditional grid mode

### Laser tube

Sealed CO<sub>2</sub> laser, power class 30-Watt

### Beam deflection

Steered beam with digital high-speed galvanometer scanners

### Focusing

Focal lengths: 64/ 95/ 127/ 190/ 254 mm (2.5/ 3.75/ 5.0/ 7.5/ 10.0 inches);  
63.5/ 85/ 100/ 150/ 200/ 300/ 351/ 400 mm (2.50/ 3.35/ 3.94/ 5.9/ 7.87/ 11.8/ 13.8/ 15.75 inches)

### Multiple operator interface options

Handheld controller  
PC software  
CLARiTY® Laser Controller  
Smart Graph Com

### Language capabilities<sup>(2)</sup>

Arabic, Bulgarian, Czech, Danish, English, German, Greek, Finnish, French, Hebrew, Hungarian, Italian, Japanese, Korean, Dutch, Norwegian, Polish, Portuguese, Romanian, Russian, Serbian, Simplified Chinese, Slovak, Spanish, Swedish, Thai, Traditional Chinese, Turkish, Vietnamese; interface dependent

### Communication

Ethernet, TCP/IP and RS232 optional  
Inputs for encoders and product detector triggers  
3 inputs/ 7 outputs for start/ stop signals, machine/ operator interlocks, alarm outputs; with additional I/Os available  
Customer-specific solutions available

### Integration

Direct integration into complex production lines via scripting interface  
Flexible beam delivery options (beam extension unit/ beam turning unit)  
Detachable umbilical for simple integration; available in 3 lengths

### Electrical requirements

100-240 VAC (autorange), -50/60Hz, 1PH, 0.70KW

### Cooling system

Air cooled

### Environment

Temperature 40-105° F (5-40° C)  
Humidity 10%-90%, non-condensing

### Sealing and safety standards

Supply Unit: IP32, optional IP54 and IP65  
Marking Unit: IP54, optional IP65  
Optional safety module provides Performance Level d (PFL-d) in accordance to EN 13849-1  
IEC/EN 60825-1:2007


### Approximate weight

Supply Unit (IP32/IP54): 16 lbs. (7 kg)  
Marking Unit (IP54): 46lbs (20.9kg)


### Applicable certifications

CE, TÜV/NRTL, FCC  
Compliance (no certification required): ROHS, CDRH/FDA

### Marking unit dimensions - IP54 with SHC60 marking head



### Supply cabinet dimensions - IP32



<sup>(1)</sup> Maximum marking and line speed is application dependent

<sup>(2)</sup> With optional CLARiTY Laser Controller

Call **800-843-3610**

Email **info@videojet.com**

or visit **www.videojet.com**

Videojet Technologies Inc.

1500 Mittel Blvd. Wood Dale IL 60191 / USA

©2014 Videojet Technologies Inc. — All rights reserved.

Videojet Technologies Inc.'s policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice. Windows is a registered trademark of Microsoft Corporation. TrueType is a registered trademark of Apple Computer, Inc.

Part No. SL000577  
3330 Spec Sheet-0414  
Printed in U.S.A.

